

IMAGETEAM™ 4600 SR/SF *Commercial/Retail Area Imager*



Features

Omni-directional reading of 1D, PDF417, MicroPDF417, Postal, Matrix, and EAN•UCC Composite codes, and OCR fonts for the easiest ever data collection.

Image Capture - Class-leading image quality and image transfer speed provide crisp images in less than one second.

Built to Last - Durable, with no moving parts. Backed by an industry leading warranty.

Connectivity – The most popular interfaces in one model. Uses the standard HHP cable set.

IQ Editing Pro™ - Provides easy integration into existing applications, without expensive host software changes.

Intelligent Aiming Options - Distinctive green aimer provides superior illumination contrast and the familiar laser aimer makes image capture applications fast and intuitive.

The IMAGETEAM™ 4600 SR/SF area imager from HHP combines the versatility of area imaging with the speed and cost of linear scanning for retail and commercial applications. Powered by Adaptus™ Imaging Technology, the IT4600 SR/SF is full featured, fast, and cost effective.

Current and future retail and commercial applications will involve much more than linear bar codes. EAN•UCC composite codes are beginning to appear in food stores; PDF codes are used for age verification in restricted item sales; and postal bar codes are used to sort mail. The omni-directional reading capability of the IT4600 SR/SF allows fast and easy reading of all these codes. Simply point and shoot. There's no need to align a scan line, or wait for a raster beam to open up.

Whether capturing a signature as proof of delivery, taking a picture for identification, or electronic data storage, image capture is an important part of current and future solutions. The IT4600 SR/SF is equipped with HHP's fourth generation imaging for best-in-class image quality and image transfer speed, all at very economical prices. Image capture has become a mainstream application requirement. Trust HHP to provide the industry's best imaging.

With no moving parts, the IT4600 SR/SF is as durable as it is versatile. HHP has a reputation for products that are tough as nails. The IT4600 SR/SF is no exception, and will provide years of service at a low cost.

To learn how the IT4600 SR/SF can work for you, contact us at any of the locations listed on the back or visit us at www.hhp.com.

Upgrade your image.



IMAGETEAM™ 4600 SR/SF Specifications

Performance

Aiming:

Red Laser Aimer: 756nm ±40nm

Green LED Aimer: 520nm ±30nm

Image: VGA, 640x480. Binary, TIFF, or JPEG output.

Working Range:

IT4600 SR	8 mil Linear (.020cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil Data Matrix (.038cm)	35 mil MaxiCode (.089cm)
Near	2.9 in. (7.4cm)	1.9 in. (4.8cm)	3.9 in. (9.9cm)	2.5 in. (6.4cm)	3.1 in. (7.9cm)	1.4 in. (3.6 cm)
Far	7 in. (17.8cm)	11.9 in. (30.2cm)	5.7 in. (14.5cm)	8.4 in. (21.3cm)	5.9 in. (15cm)	12.4 in. (31.5cm)

IT4600 SF	7.5 mil Linear (.019cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	10 mil Data Matrix (.025cm)	10 mil QR Code (.025cm)
Near	1.9 in. (4.8cm)	1.7 in. (4.3cm)	2.2 in. (5.6cm)	1.4 in. (3.6cm)	1.7 in. (4.3cm)	1.7 in. (4.3 cm)
Far	5.9 in. (15cm)	8.3 in. (21.1cm)	5.4 in. (13.7cm)	7 in. (17.8cm)	5.4 in. (13.7cm)	5.4 in. (13.7cm)

Skew Angle: ±40°

Pitch Angle: ±40°

Horizontal Velocity: 2 in. (5 cm) per second

Mechanical/Electrical

Dimensions

Length: 5.3 in. (13.5 cm)

Height: 6.2 in. (15.7 cm)

Width: 3.2 in. (8.1 cm)

Weight: 6.5 oz. (184.3 g)

Housing: UL 94V0 grade

Power Requirements: 4.5 - 12Vdc at scanner

Current Draw (Typical)	Input	Scanning	Idle
Green LED Aimer:	5 V	382mA	53mA
	12 V	157mA	44mA
Red Laser Aimer:	5 V	372mA	53mA
	12 V	157mA	44mA

Power Supply

Noise Rejection: Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

Temperature

Operating: +32°F to +122°F (0°C to +50°C)

Storage: -40°F to 140°F (-40°C to +60°C)

Humidity: 0 to 95%, non-condensing

Mechanical Shock: Operational after 50 drops from 6 ft. (1.8 m) to concrete

Ambient Light: 535 to 100,00 lux (full sunlight)


ESD Protection: Functional after 100 15kV discharges

Vibration: Withstands 5G peak from 22 to 300 Hz

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV

Laser Classification

Laser Aimer Model only: Class 2 under 21 CFR 1040.10 and 1040.11
1mW max output, 650 nm, EN60825-1: 1994+A11+A2
per MIL-HDBK-217F Ground Benign exceeds 85,000 hours



MTBF:

Symbologies

2 Dimensional: PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and EAN•UCC Composite

Linear: Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, RSS, Codablock, and BC412*

*available to licensed users

Postal: Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX (Netherlands) Post

OCR Fonts: OCR-A, OCR-B

Interfaces: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, USB, TTL level RS-232, wand emulation mode, TTL level Serial Wedge, and IBM 46XX retail terminals.

HHLIC non decoded laser output in 4600SR000 model.

True RS-232 in 4600SR030 model.

Warranty:

5 year warranty

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
sales@hhp.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
sales@hhp.com

Offices Serving Europe, Middle East, and Africa

Europe
Tel: +31 (0) 40 29 01 600
euro_sales@hhp.com
United Kingdom
Tel: +44 (0) 1 925 240055
euro_sales@hhp.com
Italy
Tel: +39 (0) 2 67 100752
euro_sales@hhp.com

France

Tel: +33 (0) 1 41 158220
euro_sales@hhp.com
Germany
Tel: +49 (0) 7 477 151377
euro_sales@hhp.com
Spain
Tel: +34 93 228 78 68
euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim

Hong Kong
Tel: +852 2511 3050
asia_sales@hhp.com
Japan
Tel: +813 5770 6312
asia_sales@hhp.com

Offices Serving Latin America

Naples, Florida
Tel: +1 239 263 7600
la-sales@hhp.com
São Paulo
Tel: +55 11 5016 3454
la-sales@hhp.com
Rio De Janeiro
Tel: +55 21 2176 0250
la-sales@hhp.com

Web Site Address www.hhp.com

Hand Held Products, Inc. d/b/a HHP ("HHP") © 1999-2004. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.