

## **IMAGETEAM™ 4800 SR/SF** *Industrial 2D Area Imager*



### **Features**

*Powered by Adaptus™ imaging technology - Delivers extraordinary reading performance to enable ease-of-use and reader versatility.*

*Aggressive, omni-directional point-and-shoot reading of linear, PDF417, and full 2D matrix symbols offers ease-of-use and greater throughput.*

*Rugged Packaging – Impact absorbent, shock resistant housing withstands fifty 6.5 foot (2 meter) drops, and is sealed to resist dust, water, and contaminants from entering the unit. Backed by an industry leading warranty.*

*Future-Proofed Technology - The versatility of Adaptus imaging technology serves broad image-based data capture needs today and protects your investment against future application demands.*

*Advanced Editing Software – Eases the transition to full 2D matrix data acquisition transfer without expensive host software modifications.*

*Intelligent Aiming Options - Distinctive green aimer provides superior illumination contrast and the familiar laser aimer makes image capture applications fast and intuitive.*

The IMAGETEAM™ 4800 Industrial 2D Area Imager is the first hand held area image reader powered by Adaptus™ Imaging Technology. Adaptus technology decodes faster, farther, and future-proofs your investment. This means your workers spend less time trying to capture data, and more time using this data to make your business more cost efficient.

Whether your application is reading conventional linear bar codes or tomorrow's 2D matrix symbologies, the IT4800 can capture them all today. If your application requires signature capture, OCR, or digital photography, the IT4800 can do it. Its advanced imaging optics software quickly and easily determines the image content and transfers it to your host system. In fact, full image transfer can be accomplished in less than one second through its on-board full speed USB interface.

The IT4800 can be used in a wide range of applications from circuit board manufacture to package delivery tracking. In addition, bar codes, images, and signature capture can provide positive proof of delivery. If discrepant material needs to be viewed by a production supplier, images can be captured and quickly transferred for immediate review and resolution, saving time and money.

Because these applications often contain challenges for many image capture devices, we have made the IT4800 extra tough. Full shock-absorbing rubber protects the imager from dozens of 6.5 feet (2 meter) drops to concrete. Many application environments exhibit airborne dust and rain, so we have sealed the IT4800 so these elements will not degrade performance. In addition to an IP54 enclosure specification, the IT4800 is backed by an industry leading warranty.

For applications that demand superior aiming, the IT4800 is the best choice. Integrated LED and laser aiming ensures the best aimer visibility for exceptional point-and-shoot performance. This ensures your operator will find and capture the correct image every time.

For additional information, contact your HHP representative at any of the locations listed on the back, or visit us at [www.hhp.com](http://www.hhp.com). Call today and see how HHP's new area imagers measure up!

**Upgrade your image.**

# IMAGETEAM™ 4800 SR/SF Specifications

## Performance

### Aiming:

Red Laser Aimer: 756nm ±40nm

Green LED Aimer: 520nm ±30nm

### Image:

VGA, 640x480. Binary, TIFF, or JPEG output.

### Working Range:

	8 mil Linear (.020cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil Data Matrix (.038cm)	35 mil MaxiCode (.089cm)
<b>IT4800SR</b>						
Near	2.9 in. (7.4cm)	1.9 in. (4.8cm)	3.9 in. (9.9cm)	2.5 in. (6.4cm)	3.1 in. (7.9cm)	1.4 in. (3.6 cm)
Far	7 in. (17.8cm)	11.9 in. (30.2cm)	5.7 in. (14.5cm)	8.4 in. (21.3cm)	5.9 in. (15cm)	12.4 in. (31.5cm)
<b>IT4800SF</b>						
Near	1.9 in. (4.8cm)	1.7 in. (4.3cm)	2.2 in. (5.6cm)	1.4 in. (3.6cm)	1.7 in. (4.3cm)	1.7 in. (4.3 cm)
Far	5.9 in. (15cm)	8.3 in. (21.1cm)	5.4 in. (13.7cm)	7 in. (17.8cm)	5.4 in. (13.7cm)	5.4 in. (13.7cm)

### Skew Angle:

±40°

### Pitch Angle:

±40°

### Horizontal Velocity:

2 in. (5 cm) per second

## Mechanical/Electrical

### Dimensions

Length: 5.3 in. (13.5 cm)

Height: 6.4 in. (16.3 cm)

Width: 3.2 in. (8.1 cm)

Weight: 7.5 oz. (213 g)

### Housing:

UL 94V0 grade

### Power Requirements:

4.5 - 12Vdc at scanner

### Current Draw (Typical):

Input	Scanning	Idle
5 V	382mA	53mA
12 V	157mA	44mA

### Green LED Aimer:

5 V	372mA	53mA
12 V	157mA	44mA

### Red Laser Aimer:

5 V	372mA	53mA
12 V	157mA	44mA

## Power Supply

### Noise Rejection:

Maximum 100mV peak to peak, 10 to 100 kHz

## Environmental

### Temperature

Operating: 14°F to +122°F (-10°C to +50°C)

Storage: -40°F to 140°F (-40°C to +60°C)

### Humidity:

0 to 95%, non-condensing

### Sealing:

IP54 (water and dust resistant)

### Mechanical Shock:

Operational after 50 drops from 6.5 ft. (2 m) to concrete

### Ambient Light:

535 to 100,00 lux (full sunlight)

### ESD Protection:

Functional after 100 discharges at 15kV

### Vibration:

Withstands 5G peak from 22 to 300 Hz


### Agency:

FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV

### Laser Classification

#### Laser Aimer Model only:

Class 2 under 21 CFR 1040.10 and 1040.11  
1mW max output, 650 nm, EN60825-1: 1994+A11+A2  
per MIL-HDBK-217F Ground Benign exceeds 82,000 hours



### MTBF:

## Symbologies

### 2 Dimensional:

PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and EAN•UCC Composite.

### Linear:

Codabar, Code 39 including PARAF, Interleaved 2 of 5, Code 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, RSS.

### Postal:

Postnet, Planet Code, British Post, China Post, Canadian Post, Japanese Post, KIX (Netherlands) Post

### OCR Fonts:

OCR-A, OCR-B

### Interfaces:

All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, TTL level RS-232, TTL level Serial Wedge, USB, wand emulation, HHLC non-decoded laser compatible, True RS-232, IBM 468x, and IBM469x.

### Warranty:

5 year warranty

## Worldwide Offices

### Offices Serving North America

Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America: +1 800 582 4263  
sales@hhp.com  
Charlotte, NC  
Tel: +1 704 998 3998  
or, in North America: +1 800 582 4263  
sales@hhp.com

### Offices Serving Europe, Middle East, and Africa

Europe  
Tel: +31 (0) 40 29 01 600  
euro\_sales@hhp.com  
United Kingdom  
Tel: +44 (0) 1 925 240055  
euro\_sales@hhp.com  
Italy  
Tel: +39 (0) 2 67 100752  
euro\_sales@hhp.com

### France

Tel: +33 (0) 1 41 158220  
euro\_sales@hhp.com  
Germany  
Tel: +49 (0) 7 477 151377  
euro\_sales@hhp.com  
Spain  
Tel: +34 93 228 78 68  
euro\_sales@hhp.com

### Offices Serving Asia and the Pacific Rim

Hong Kong  
Tel: +852 2511 3050  
asia\_sales@hhp.com  
Japan  
Tel: +813 5770 6312  
asia\_sales@hhp.com

### Offices Serving Latin America

Naples, Florida  
Tel: +1 239 263 7600  
la-sales@hhp.com  
São Paulo  
Tel: +55 11 5016 3454  
la-sales@hhp.com  
Rio De Janeiro  
Tel: +55 21 2176 0250  
la-sales@hhp.com

Web Site Address [www.hhp.com](http://www.hhp.com)

Hand Held Products, Inc. d/b/a HHP ("HHP") © 1999-2004. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.