

SCANTEAM® 2000/R Series

POS Interface

Bar Code, Magnetic Stripe & MICR Interface



Features

Universal Interface for POS, Computer Terminals and PCs - Provides bar code, mag stripe and MICR input to existing terminals and an upgrade path which protects against obsolescence.

Data Capture from a Variety of Devices - Easy integration of all types of data collection for most terminals and PCs. Data capture for bar code, triple track magnetic stripe and MICR from checks, and RS-232 devices.

Programmable Data Formatting - Bar code, mag and MICR output can be formatted to match multiple terminal programs and protocols.

ASIC and FLASH E²PROM - In-field firmware changes do not require chip changes. New code is loaded into the ST2000's FLASH memory through the aux interface connector.

Compact Size - Smaller footprint maximizes work station space.

The SCANTEAM® 2000 Series is a versatile, compact and rugged interface which adds bar code, mag stripe and MICR automatic data entry capability to IBM, NCR, Fujitsu, Nixdorf and other popular POS terminals, PCs and CRT terminal-based systems. The ST2000 supports keyboard wedge, parallel (OCR), single and dual port serial RS-232, OCIA and IBM 4680 synchronous interfaces.

The two scanner ports accept all types of hand held bar code scanners including HHP SCANTEAM Series solid state lasers, contact wand scanners, the ST3400 CCD scanner, and the ST8300 MICR check reader. Dual or triple track credit card data input from the ST6901 is via the MSR port; RS-232 data input is via a bidirectional auxiliary port.

The ST2000 Series is fully programmable, allowing data input to be formatted according to an application's program definitions. Its advanced data formatting capability and universal design protects against obsolescence.

The SCANTEAM® 2000 Series, which interfaces to most POS and mainframe terminals, as well as PC systems, enhances productivity and increases accuracy in a wide variety of retail applications. Sales data is quickly and accurately collected, increasing customer satisfaction and enhancing the retailer's competitiveness. In the "back room," in-store and distribution center receipts are quickly reconciled, reducing shortages and time in the receiving cycle.

Data format and FLASH E²PROM firmware can be field programmed via bar code menu, cloned, or factory set to ensure compatibility with applications, now and in the future. The RS-232 port allows input from in-counter or presentation style scanners, portable data collectors, MICR check readers and PIN pads with full edit capability. Mag stripe data from tracks 1, 2, and 3 can be selected/edited to meet credit card issuer requirements, now and as they change. MICR data can be edited to meet the requirements of a check authorization system.

Upgrade your image.

SCANTEAM® 2000/R Series Specifications

Mechanical/Electrical

Dimensions

| | |
|-------------------|---|
| Weight: | 6.4 oz. (181.4g) |
| Height: | 1.0 in (2.5 cm) |
| Length: | 4.0 in. (10.2 cm) |
| Width: | 3.9 in. (10.0 cm) |
| Enclosure: | Lexan®, a G.E. Polycarbonate thermoplastic; UV stabilized |
| Color: | Pearl White |

Power Requirements

| | |
|------------------------------|---|
| Electrical: | Complies with UL, CSA, and VDE |
| Power Supply Options: | +5V supplied from the terminal or optional power supply, which may be required in some cases. |
| Output: | +5VDC |
| Current Draw: | 2000/R 150mA typical; 2000/C 140mA typical |
| Connectors: | Scanner Ports (2): 9 pin D male, squeeze-to-release Magnetic Stripe Port: 8 pin modular Power: 4 pin Mini-Din I/O: 40 pin high density |

Environmental

Temperature

| | |
|------------------------------------|--|
| Operating: | 32°F to 104°F (0°C to 40°C) |
| Storage: | -40°F to 212°F (-40°C to 100°C) |
| Humidity: | 0% to 95% non-condensing |
| Shock: | Functions normally after ten 3 ft. drops onto a concrete surface |
| EMI Radiation: | FCC Class A and *EN55022 Class B (1988) |
| ESD Sensitivity: | Meets *IEC 801-2; 1991/1984 and a minimum of 300 discharges at 2.5kv intervals from 2.5kv to 17.5kv. |
| Radiated Susceptibility: | Meets *IEC 801-3; 1984 |
| Electrical Fast Transients: | Meets *IEC 801-4; 1988 |

*These requirements combined with EN50082-1; 1992 indicate conformity to the EMC Directive 89/336/EEC.

Interfaces

| | |
|------------------------------|---|
| Parallel (OCR): | All IBM, Fujitsu, others |
| OCIA: | NCR short and long format, Nixdorf, others |
| IBM: | 4683/4; Port 5B, 9B and 17 |
| Keyboard Wedge | |
| POS: | NCR 2151, 2152, 2154/55, 2950, 7052; IBM 3653, 3683/4 and others |
| PC: | IBM PC/XT/AT, PS/2 and compatibles |
| Terminals: | IBM 3151, 316X, 319X, 347X IDEAS, X77, 276, I/O 88/122 and others |
| Serial: | Bidirectional RS-232 serial or serial wedge |
| Input Devices: | HHP laser, CCD and wand scanners, ST6901 dual or triple track magnetic stripe reader, ST8300 MICR check reader, RS-232 (input), other industry standard devices. |
| Data Format: | Full user programming for data edits including multiple formats within symbologies, Mag Stripe Tracks 1, 2, and 3 and MICR data. |
| Programming: | Bar code menu, PC download, clone mode, factory |
| Parameter Selections: | Data edit with cursor control, search, insert, delete, locate, fill, truncate, and delimiters for all inputs. Terminal type and port, keyboard style and function keys, RS-232 protocol. MICR data parsing including transit, account and check number. |
| Symbologies Decoded: | UPC-E, UPC-A, EAN, ISBN all versions with supplement suppression, Code 39, Code 128, Interleaved 2 of 5, Matrix 2 of 5, Code 11, Code 93, MSI, Plessey, and Codabar |

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
sales@hhp.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
sales@hhp.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
euro_sales@hhp.com
United Kingdom
Tel: +44 (0) 1 925 240055
euro_sales@hhp.com
Italy
Tel: +39 (0) 2 67 100752
euro_sales@hhp.com

France
Tel: +33 (0) 1 41 158220
euro_sales@hhp.com
Germany
Tel: +49 (0) 7 477 151377
euro_sales@hhp.com
Spain
Tel: +34 93 228 78 68
euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050
asia_sales@hhp.com
Japan
Tel: +813 5842 6325
asia_sales@hhp.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
la-sales@hhp.com
São Paulo
Tel: +55 11 5016 3454
la-sales@hhp.com
Rio De Janeiro
Tel: +55 21 2494 7060
la-sales@hhp.com

Web Site Address www.hhp.com

Hand Held Products, Inc. d/b/a HHP ("HHP") ©1999-2003. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.