

Magellan® 8100Ω

With OmegaTek™ Productivity Technology



Features:

- OmegaTek™ Productivity Technology
- Enhanced All-Weights™ Platter
- Aggressive & ergonomic 5-sided scanning
- Supports all popular host interfaces
- FirstStrike™ Advanced Decoding Software
- Flash memory for easy, low cost upgrades
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Host Download
- Diagnostic Reporting
- RSS Decoding
- Optional EAS functionality
- Sunrise 2005 Compliant



"Nothing Beats a Magellan®"

Mechanical

Length & Weight

| Model | Scanner/Scale | Length | Weight |
|-------|--------------------|-----------------|--------------------|
| 8100Ω | short scanner | 13.9" / 35.3 cm | 13.0 lbs. / 5.9 kg |
| 8101Ω | medium scanner | 15.7" / 39.9 cm | 15.0 lbs. / 6.9 kg |
| 8102Ω | med. scanner/scale | 15.7" / 39.9 cm | 18.0 lbs. / 8.2 kg |
| 8103Ω | long scanner | 20.0" / 50.8 cm | 15.0 lbs. / 6.9 kg |
| 8104Ω | long scanner/scale | 20.0" / 50.8 cm | 20.0 lbs. / 9.1 kg |

Width: 11.5" / 29.2 cm

Depth (below counter): 4.0" / 10.2 cm

Height (above counter): 51" / 13.0 cm

Scale Capacities

Capacity: 30.0 lbs. / 999 kg – 15 kg (interface dependent)

Minimum increment: 0.01 lb. / 0.005 kg

Vibration immunity: 4 programmable filter settings

Maximum static weight: 150 lbs. / 68 kg

Adjustments required: Calibration only

Optical

Scan lines: 48

Motor speed: 4500 rpm

Scan rate: 3,600 lines/sec.

Scan zone: 360°

Sides read: 5

Read height: 6.0" / 15.2 cm

Environmental

Temperature rating

Operating: 50° to 104° F / 10° to 40° C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Decoding Capability

The Magellan® 8100Ω autodiscriminates between the following supported symbologies:

- UPC Versions A & E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- Reduced Space Symbology (RSS-14, expanded & stacked)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- Interleaved 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey

Data Sheet

Electrical

AC Power requirements:

100-250 VAC, 50-60 Hz

8 Watts (nominal)

12 Watts (maximum)

4 Watts (sleep mode)

Communications

Host: Choose from: IBM 46XX, RS-232, or IBM USB.

Other:

Powered RS-232 auxiliary port

Scale host port

Remote scale display port

EAS interlock port

Safety & Regulatory

Electrical: IRAM (Argentina), AS/NZS 60950 (Australia); CSA-C22.2 No. 60950 (Canada); EN60 950 (TÜV Europe); PSE Mark (Japan); UL 60950 (USA)

Emissions: FCC part 15, Class B (USA); AS/NZS 3548 (Australia/New Zealand); EN 55022-B (Europe); CISPR 22-B, VCCI-B (Japan)

Laser safety: Class IIa Laser Product

(CAUTION: Laser Light – do not stare into beam); IEC 825 Class 1, EN60 825 Class (Europe)



Weights and Measures: Australia; Canada; 90/384/EEC (Europe); Mexico; New Zealand; USA (NIST Handbook 44)

Contact your PSC representative for certification schedule and additional listings.

Other

EAS compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint® Systems.

Good Read acknowledgement with Sensomatic®.

PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

